

# G7 BRIDGE

# MONITOR EMPLOYEE SAFETY ANYWHERE

#### Portable Satellite & Cellular Base Station

The Blackline Safety G7 Bridge is a portable base station that provides a satellite and cellular uplink for G7x and Loner 900 monitoring devices.

One G7 Bridge can link up to five G7x or Loner 900 devices. G7 Bridge communicates with devices through an industrial-quality 900 MHz radio link. The employee worn monitoring devices can work up to 2 km away from G7 bridge, even inside complex facilities.

Through Iridium satellites or 3G cellular data, G7 Bridge communicates with the Blackline Safety Network. The transition to satellite communication is automatic when working beyond cellular networks, ensuring seamless monitoring. Equipped with GPS location technology, it provides your organization with a simple alternative to elaborate fleet management systems. G7 Bridge can mass-notify employees of the need to evacuate, connect workers to monitoring personnel via two-way messaging and account for teams on a real-time map, to best leverage available resources when help is needed.

The Blackline Safety Network monitors remote worker safety around-the-clock. It includes communication networks, our Blackline Live™ web portal, your user account and monitoring devices. Through Blackline Live, create and customize configuration profiles for G7 Bridge and connected G7x or Loner 900 devices.

G7 Bridge is self-powered and portable, allowing you to quickly move it from one vehicle to another, such as from a truck to an all-terrain vehicle. It has your teams' back at all times, no matter their location.

## **Features**





Portable

Weatherproof design





Dual mode communications

900 MHz communications





 ${\sf TeamAlert}$ 

Two-way messaging



# DETAILED SPECIFICATION

#### Size & Weight

**Size**: 73 mm x 107 mm x 141 mm (2.87"x 4.21"x 5.55") Measurements do not include mount **Weight**: 540 q (19.04 oz)

#### **Buttons & Indicator Lights**

Power button: Power on/off
Red light plus buzzer: Safety alert
Green SureSafe™ light: Blinking (powered),
continuous (connected)

**LCD Screen:** Display menu, battery status, backhaul link status

Menu Navigation buttons: Up, Down, OK

#### **User Notification**

**Indicators:** Acoustic buzzer, indicator lights **LCD Screen:** Display notifications/messages from backend

#### Wireless Communication

Radio: UMTS 800/850/900/1900/2100; Quad-band GSM/GPRS 850, 900, 1800, 1900; Iridium Satellite (1621 MHz); ISM band radio (915 MHz) 900 MHz Radio: Americas: 902 – 928 MHz Australian/

Now 700 and 016 027 MHz 1 Watt

New Zealand: 916 – 927 MHz, 1 Watt

Antenna: Internal

#### **Location Technology**

GPS Radio: 72 channel high sensitivity
GPS Accuracy: ~5 m (16 ft) outdoors, ~50 m (165 ft) indoors

GPS Real-time location turnaround time:

~20 seconds Assisted GPS

#### 900 MHz Radio Link Range

General use: up to 2 km

**Hilltop to hilltop:** 10+ km Terrain, foliage, and buildings will affect overall 900 MHz radio link range

#### **Alert Messages**

Emergency/Low battery/Power off/Text messages

### **Mobile Messaging Methods**

Remote messaging by email or SMS

## Power & Battery

Rechargeable Li-ion battery: 6800 mAh capacity
Battery Life: 50 hours @ 20°C (68°F); 44 hours @ -20°C
(-4°F); 14 hours @ -40°C (-40°F); It is recommended
that the hard wire kit is used anytime below -20°C
Charging connector: Micro USB

#### **Environmental**

Storage temperature:  $-30^{\circ}\text{C}$  to  $75^{\circ}\text{C}$  ( $-22^{\circ}\text{F}$  to  $167^{\circ}\text{F}$ ) Operating temperature:  $-40^{\circ}\text{C}$  to  $55^{\circ}\text{C}$  ( $-40^{\circ}\text{F}$  to  $131^{\circ}\text{F}$ ) Charging temperature:  $0^{\circ}\text{C}$  to  $45^{\circ}\text{C}$  ( $32^{\circ}\text{F}$  to  $113^{\circ}\text{F}$ ) Ingress Protection: Designed to meet IP65

#### **Regulatory Compliance**

FCC, IC, RCM, RoHS

Contains: FCCID: XPYICGM5NNN, Q639603, KQNMLINK900, IC: 8595A-ICGM5NNN, 4629A-9603, 2361A-MLINK900

#### **Device Requirements**

Activated service plan, satellite communications requires line-of-sight to sky, GPS for locating

#### Warranty

Two-year limited factory warranty

#### Wireless coverage and service plans

Cellular coverage: Nearly 150 countries

Satellite coverage: Global

 $\textbf{900 MHz operation:} \ \mathsf{ITU} \ \mathsf{Region} \ 2, \ \mathsf{Australia}, \ \mathsf{New}$ 

7ealand

Service plan options: Contact Blackline

#### **Blackline Live Web Application**

Cloud-hosted safety monitoring web application is highly customizable for every customer requirement. Includes live map, employee address book, user roles, alert management, device configurations, alert setups and reporting.