



# G7 DOCK

## Connected Gas Calibration and Bump Testing

Blackline Safety's G7 Dock is the solution to easily calibrating, bump testing and charging G7 devices. Docks can be used with both G7c and G7x devices, and supports G7 Single-gas and Quad-gas cartridges.

G7 Dock requires no initial setup — all communications and configurations work out of the box. Managing calibrations and bump tests is easy using the G7 device's LCD screen and menu system. G7 Dock leverages Blackline's cloud-hosted monitoring portal for configuration and to store test data for compliance tracking and reporting.

With G7 Dock, bump tests and calibrations are straightforward, performed by simply placing G7 into the dock. If a G7 device is due for a bump test and/or calibration, it will automatically perform the required test actions when placed into the dock and the lid closed. All test results are communicated in real-time to the user's Blackline Live account after bump tests and calibrations are complete.

Blackline Live makes it easy to manage changes to G7 Dock inlet configurations. Many organizations leverage the convenience of multi-gas mixtures while others employ single-gas cylinders for the improved cost of detector testing and calibration. The default configuration is a multi-gas mixture that also supports single-gas setups. Each dock has five ports at the back of the device — four gas inlets and one outlet for exhausting calibration gas. G7 Dock is configurable to manage up to four single-gas cylinders.

Blackline Safety designed G7 Dock to provide economical use of calibration gas, with a low flow rate.

### Features



Bump test



Calibrations



Charging




Easy setup



Blackline Live™  
web portal



Easy inlet  
configuration



Quick-connects



## DETAILED SPECIFICATION

### Size & Weight

Size: 215mm x 100mm x 95mm (8.46", 3.94", 3.74")  
Weight: 202g (7.1oz)

### Mounting

Wall mounting  
Desk mounting  
Technical user guide includes mounting template

### Gas interface configuration

Four customizable gas inlets, one purge port

### Internal pumps

Exhaust diaphragm pumps

### Bump test

25-second bump test, less than 10 seconds of gas applied during a bump

### Calibration

Four minute calibration, less than two minutes of gas applied during a calibration

### Gas Usage

Optimized gas delivery (estimated flow 300ml/min)

### Power Supply

Input voltage: 5 VDC @ 1000 mA  
Power connector: Micro-USB  
120/240 VAC power adaptor and USB cable included

### Regulatory Compliance

C-Tick | CAN ICES-3(B)/NMB-3(B) | FCC | CE

### Warranty

Two year warranty

### Blackline Live Web Application

Cloud-hosted safety monitoring web application is highly customizable for every customer requirement. Includes live map, employee address book, user roles, alert management, device configurations, alert setups and reporting.

## HIGHLIGHTS

- Over-the-air configuration updates
- Manage all dock configurations through Blackline Live web portal
- Automatic bump tests
- Automatic calibrations
- Dock usage reports via Blackline Live
- Gas usage reports via Blackline Live
- Doubles as a charging station for G7 devices