

GasAlert100

H₂S or CO

"INNOVATORS IN GAS DETECTION"

BWF

Technologies



100 Day Disposable Gas Detector



ACTUAL SIZE



Protect Yourself

- △ 100 days of protection with no maintenance costs—ideal for employees and contractors for short-term work projects
- △ Continuous, alphanumeric LCD shows detector life remaining, alarm setpoints and advises self-test status
- △ Records and displays the peak alarm encountered and the time elapsed since the event occurred
- △ Confidence LCD display advises instrument is on and functioning
- △ Two alarm levels (low/high)
- △ Wide-angled visual alarm bar visible from all angles
- △ Provides 95 dB (typical) alarm tone
- △ Compact (1.0 x 1.45 x 2.3 inches / 26 x 37 x 58 mm) and lightweight (1 oz. / 30 g)
- △ Maintenance free—no sensor or battery replacement, no calibration, no down time
- △ Full function self-test of: audible/visual alarms plus integrity of sensor, battery and circuitry
- △ Continuously on—one button activation and test
- △ High-tension stainless steel pocket/belt clip
- △ Instructions in local languages included



CLASSIFIED
UL
c US

ATEX



and
others

Ordering Information

GA100-H 100 day H₂S detector

GA100-M 100 day CO detector

Note: Models above are available with special alarm setpoints.

Accessories

GA-TS04 GasAlert100 automatic test station

GA-HC-1 Hard hat clip

GA100-CDT Interactive product demo CD-ROM



www.gasmonitors.com

Email: info@bwt.net

GasAlert100

H₂S or CO

100 Day Disposable Gas Detectors

The GasAlert100 is a practical, cost-effective solution to short-term work projects. The GasAlert100 provides 100 days of continuous, maintenance-free operation from the day of activation. Operated by an advanced microcontroller and electrochemical sensor, GasAlert100 is equipped with two levels of alarm and a continuous, alphanumeric confidence LCD.

Simply press the START/TEST button and the GasAlert100 is ready for use. The life remaining is displayed in days and then hours. The full function self-test verifies sensor, circuit and battery integrity and audible/visual alarms. Alarm setpoints are displayed on command.

The rugged, compact GasAlert100 is designed with the most advanced RFI protection available in industry today. Simply clip the instrument to your lapel, pocket, belt or hard hat for unequalled protection.

SPECIFICATIONS

DETECTOR: Disposable, zero-maintenance gas detector

Model:	GasAlert100 H ₂ S	GasAlert100 CO
Operational life ¹ :	100 days	100 days
Sensor range:	0-100 ppm	0-300 ppm
Low alarm level ² :	10 ppm	35 ppm
High alarm level ² :	15 ppm	200 ppm
Operating temperature:	-22 to +113 °F -30 to +45 °C	+5 to +113 °F -15 to +45 °C
Calibration:	Not required	

¹Given 3-5 minutes of alarm per day in normal operation

²Customer special alarm settings available

Continuously on: Yes
 One-button control: Activation and self-test
 Full function self-test: Verifies sensor, circuitry and battery integrity and audible/visual alarms
 Sensor: Electrochemical cell (temperature compensated)

INDICATORS AND ALARMS

Visual gas alarm: Flashing, wide-angled alarm lens with dual red LEDs plus ALARM LCD readout
 Audible gas alarm: Pulsing siren 95 dB at 1 ft./0.3 m (typical)
 Failure alarm: Yes (audible/visual)
 Self-test pass: Yes (audible/visual)
 Other: End of life (audible/visual)

CONTINUOUS LCD DISPLAY:

Alphanumeric status panel LCD advises:
 Gas monitored: H₂S or CO
 Life remaining: Continuously displayed in days and then hours
 Two alarm levels: LOW alarm / HIGH alarm
 Peak alarm levels: Records and displays peak alarm exposure, and time elapsed (up to 24 hrs.)
 Alarm setpoints: High and low (displayed on demand in ppm)
 Self-test status: Advises to "TEST" and that self-test was passed "✓"

TESTS

Full function self-test: On demand, as often as once every 20 hours and on activation
 Battery: Every two hours (auto)

GENERAL SPECIFICATIONS:

Impact-resistant ABS enclosure
 Ingress Protection: IP65
 Humidity: 5% to 95% RH (non-condensing)
 EMI/RFI: Complies with EMC Directive 89/336/EEC
 Battery: Lithium, non-replaceable
 Size: 1.0 x 1.45 x 2.3 inches / 26 x 37 x 58 mm
 Weight: 1 oz. / 30 g

WARRANTY: 100 days from activation plus 1 year shelf life

DUE TO ONGOING RESEARCH AND PRODUCT IMPROVEMENT, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

RATINGS AND CERTIFICATIONS: (Intrinsic safety)  Class I, Div. 1, Gr. A, B, C, D

ATEX: CE  II 1 G
EEx ia IIC T4

"INNOVATORS IN GAS DETECTION"



For further information:

1-888-749-8878 USA
 1-800-663-4164 Canada
 +44 (0) 1869 233004 Europe
 +971-4-8871766 Middle East
 +61-438-887-232 Australia
 +852-2974-1783 China
 +65-9737-2005 South East Asia
 +1-403-248-9226 Other Countries

Corporate Headquarters

2840 - 2 Avenue S.E.
 Calgary, AB, Canada T2A 7X9
 Phone: +1-403-248-9226
 Fax: +1-403-273-3708

E-mail: info@bwt.net.com
 www.gasmonitors.com

BW1030-01-01-00-8.25x11-20050215-5240-6

- FULL FUNCTION DAILY SELF-TEST
- TWO LEVELS OF GAS ALARM
- 95 dB AUDIBLE ALARM (TYPICAL)
- SUPERIOR RFI PROTECTION
- RUGGED ENCLOSURE
- ADVANCED MICROCONTROLLER OPERATION
- BRIGHT, WIDE-ANGLED VISUAL ALARM BAR



Interactive Product Demo CD-ROM


Full information STATUS panel



▲ Displays life remaining in days and hours



▲ Advises alarm level encountered (LOW/HIGH)



▲ Display automatically advises self-test is due



▲ Displays alarm setpoints in ppm

Locally distributed by:

