



# GasAlertMicro

multi-gas detector



## Versatile multi-gas

Combining both performance and affordability, the GasAlertMicro has a comprehensive range of features and flexible power options. The wide variety of field-adjustable user options include passcode protection for tamper-proof operation. Suited to a wide range of applications, the GasAlertMicro offers a simple, automatic calibration procedure and is compatible with BW's MicroDock II automatic test and calibration system.



H<sub>2</sub>S

CO

O<sub>2</sub>

SO<sub>2</sub>

LEL




- Field-proven reliability with straightforward operation
- Three interchangeable power options, minimal downtime and convenient flexibility
- Extensive datalogging capacity

**BW**  
Technologies  
by Honeywell

Wear yellow. Work safe.

### Standard features of BW products:

- Continuous LCD shows real-time gas concentrations
- Compact and lightweight design makes it comfortable to wear
- Simple automatic calibration procedure; compatible with BW MicroDock II automatic test and calibration station
- Full function self-test of sensor, battery status, circuit integrity and audible/visual alarms on start up
- Bright wide-angled visual alarm bars
- Built-in concussion-proof boot

<b>GasAlertMicro Specifications</b>																			
<b>Size</b>	2.4 x 4.0 x 1.3 in. / 6.0 x 10.0 x 3.3 cm																		
<b>Weight</b>	7.4 oz. / 211 g																		
<b>Temperature</b>	-4 to +122°F / -20 to +50°C																		
<b>Humidity</b>	5% - 95% RH (non-condensing)																		
<b>Alarms</b>	- Visual, vibrating, audible (95dB) - Low, High, STEL, TWA, OL (over limit)																		
<b>Tests</b>	Sensor integrity, circuitry, battery and audible/visual alarms on activation, battery (continuous)																		
<b>Pump</b>	Compatible with the Sampler motorized sampling pump																		
<b>Typical battery life</b>	AA alkaline: 16 - 18 hrs GA MicroBatt: 16 - 18 hrs Rechargeable: 14 - 16 hrs																		
<b>User options</b>	<table border="0"> <tr> <td>Confidence beep</td> <td>Automatic backlight</td> </tr> <tr> <td>Set STEL interval</td> <td>Combustible gas measurement (% LEL or % by volume methane)</td> </tr> <tr> <td>Sensor on/off</td> <td></td> </tr> <tr> <td>Latching alarms</td> <td>User-settable calibration gas level</td> </tr> <tr> <td>Safe display mode</td> <td></td> </tr> <tr> <td>Stealth mode</td> <td>Bump test due reminder</td> </tr> <tr> <td>Passcode protection</td> <td>Language choices (5)</td> </tr> <tr> <td>O<sub>2</sub> auto calibration on start up</td> <td>Adjust clock</td> </tr> <tr> <td>MicroBatt mode</td> <td>Set datalogger rate</td> </tr> </table>	Confidence beep	Automatic backlight	Set STEL interval	Combustible gas measurement (% LEL or % by volume methane)	Sensor on/off		Latching alarms	User-settable calibration gas level	Safe display mode		Stealth mode	Bump test due reminder	Passcode protection	Language choices (5)	O <sub>2</sub> auto calibration on start up	Adjust clock	MicroBatt mode	Set datalogger rate
Confidence beep	Automatic backlight																		
Set STEL interval	Combustible gas measurement (% LEL or % by volume methane)																		
Sensor on/off																			
Latching alarms	User-settable calibration gas level																		
Safe display mode																			
Stealth mode	Bump test due reminder																		
Passcode protection	Language choices (5)																		
O <sub>2</sub> auto calibration on start up	Adjust clock																		
MicroBatt mode	Set datalogger rate																		
<b>Ratings</b>	EMI/RFI: Complies with EMC Directive 89/336/EEC IP 65																		
<b>Certifications and approvals</b>	<p>  Class I, Div. 1, Gr. A, B, C, D   American Bureau of Shipping  <b>ATEX:</b>  II 1 G T4*                      Ex ia IIC T4*  <b>IECEX:</b> Ex ia IIC T4*  <b>BAM:</b> Certified by BAM to the O<sub>2</sub>, H<sub>2</sub>S, CO and combustible performance standards  <b>CE:</b> European Conformity  <i>*Temperature codes may vary as a function of the batteries installed. Please see owner's manual for a complete listing of compatible batteries and codes.</i> </p>																		
<b>Warranty</b>	Full 2 year warranty including all sensors																		

### Additional GasAlertMicro features:

- Compatible with the Sampler motorized pump for remote sampling
- Equipped with internal vibrating alarm for high noise areas
- Powered by two AA alkaline, two AA rechargeable NiMH cells or GA MicroBatt rechargeable battery pack
- Multi-language support in English, French, German, Spanish, and Portuguese
- Stealth model available with black housing and infrared LEDs

### Options and Accessories



MicroDock II compatible



Battery Packs



Dual Battery Charger




Confined Space Kit

For a complete list of accessories, please contact BW Technologies by Honeywell.

<b>Sensor Specifications</b>		
Gas	Measuring Range	Resolution
<b>H<sub>2</sub>S</b>	0-100 ppm	1 ppm
<b>CO</b>	0-500 ppm	1 ppm
<b>O<sub>2</sub></b>	0-30.0%	0.1%
<b>SO<sub>2</sub></b>	0-100 ppm	1 ppm
<b>Combustible gases</b>	0-100% LEL 0-5.0% v/v	1% 0.1%

Alarm set points for all sensors are user adjustable. Set point(s) are automatically displayed during instrument start up.

### Locally available from



### Corporate Headquarters

2840 - 2 Avenue S.E.  
Calgary, AB, Canada T2A 7X9  
Phone: +1-403-248-9226

USA 1.888.749.8878  
Canada 1.800.663.4164  
Australia +61.3.9464.2770

Europe +44 (0)1295 700 300  
France +33 (0) 442 98 17 70  
Middle East +971-4-8871766

China +86 10 6786 7305  
S.E. Asia +65 6580 3468  
Other Countries +1-403-248-9226

[www.gasmonitors.com](http://www.gasmonitors.com)

[info@gasmonitors.com](mailto:info@gasmonitors.com)

DUE TO ONGOING RESEARCH AND PRODUCT IMPROVEMENT, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.