



Single Gas Clip

Whether it's the hottest environment or the coldest, our Single Gas Clip is designed and tested to provide worker safety in the harshest working conditions.

At Gas Clip Technologies, we enhance customer safety by using the latest technology. We test 100% of our portable

gas detectors, not just a random sample of units. That's why we can offer a low cost of ownership on our gas detectors.

There are no hidden service charges, no maintenance fees—just reliable units that will help your facility workers and contractors do their jobs safely, productively and cost effectively.



- ▶ Unmatched sensor reliability for H₂S, CO, & O₂
- ▶ Adjustable alarm set points and real-time gas reading capability
- ▶ 50% larger battery capacity
- ▶ 0.1 ppm resolution for sensor and display
- ▶ Two-way IR comms for event downloads, bump tests & updates
- ▶ Programmable unit identification
- ▶ "Bump check" confirmation/identification

For unmatched safety, reliability and productivity, choose the world's most advanced single gas detector: the Single Gas Clip.



Portable gas detectors you can count on.

gascliptech.com ♦ Toll-free: 877.525.0808 ♦ 972.775.7577 ♦ Fax: 972.775.2483



IR Reader



“Clip Dock” Docking Station

Specifications

SIZE	85.6 mm H x 50 mm W x 29.2 mm D 3.37 in H x 1.97 in W x 1.15 in D
WEIGHT	76g 2.7 oz
TEMPERATURE	H ₂ S: -40°C to +50°C/-40°F to +122°F CO: -40°C to +50°C/-40°F to +122°F O ₂ : -35°C to +50°C/-31°F to +122°F
HUMIDITY	5% to 95% non-condensing relative humidity
ALARMS	Visual, vibrating, audible (minimum 95dB)
TESTS	Full function self-test on activation and every 20 hours; continuous automatic battery tests
BATTERY LIFE	Two years
RATINGS	EMC Directive 2004/108/EC IP66/67
CERTIFICATIONS	Standard(s): UL-913 & CAN/CSA-C22.2 No. 157
	ETL CLASSIFIED  Intertek 4003191
	Class 1 Divisions 1 & 2, Groups A, B, C and D
	ATEX: II 1 G Ex ia IIC T4
	IECEX: EX ia IIC T4
WARRANTY	2 years from activation 1 year shelf life
H₂S	Measuring range: 0-100 ppm Low alarm limit: 10 ppm High alarm limit: 15 ppm
CO	Measuring range: 0-300 ppm Low alarm limit: 35 ppm High alarm limit: 200 ppm
O₂	Measuring range: 0-30% (volume) Low alarm limit: 19.5% High alarm limit: 23.5%
NOTES	Real-time gas display or time remaining; adjustable alarm set points and bump check reminder



Portable gas detectors you can count on.

gascliptech.com ♦ Toll-free: 877.525.0808 ♦ 972.775.7577 ♦ Fax: 972.775.2483

2012 © Gas Clip Technologies, Inc. All Rights Reserved.

Distributed By: