

According to Regulation (EC) No. 1907/2006 OSHA Regulation 29 CFR 1910.1200 Canadian Regulation SOR/88-66

Revision Date: 2013-03-13

Reason for Revision: Regulation (EC) No. 1272/2008 Compliance

SECTION 1: IDENTIFICATION OF THE PRODUCT AND COMPANY

Product Name: HI 93753A-0 Displacing Reagent

Application: Determination of Chloride in Water Samples

Company Information (USA):

Hanna Instruments, Inc.

584 Park East Dr. Woonsocket, Rhode Island, USA 02895

Technical Service Contact Information: 1-800-426-6287 (8:30AM - 5:00PM ET)

+1-401-766-4260 (8:30AM - 5:00PM ET)

USA Emergency Contact Information: 1-800-424-9300 (Chemtrec 24Hr. Emergency)
International Emergency Contact Information: +1-703-527-3887 (Chemtrec 24Hr. Emergency)

E-mail Address: tech@hannainst.com

SECTION 2: HAZARD IDENTIFICATION

Harmful if swallowed. Harmful in contact with skin. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.

According to Regulation (EC) No. 1272/2008:

Classification: Acute Toxicity, Oral (Category 4)

Acute Toxicity, Dermal (Category 4)

Specific Target Organ Toxicity, Repeated Exposure (Category 2)

Chronic Aquatic Toxicity (Category 3)

Signal Word: Warning

Pictograms:



Hazard H302: Harmful if swallowed.
Statements: H312: Harmful in contact with skin.

H373: May cause damage to organs through prolonged or repeated exposure.

H412: Harmful to aquatic life with long lasting effects.

PrecautionP280: Wear protective gloves/eye protection/face protection.Statements:P308+P313: IF exposed or concerned: Get medical advice/attention.

According to Directives 67/548/EEC and 1999/45/EC:

Symbol: Xn: Harmful

R-phrases: 20/21/22-33-52/53: Harmful by inhalation, in contact with skin and if swallowed. Danger of cumulative effects. Harmful

to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S-phrases: 28-36-45-60: After contact with skin, wash immediately with plenty of water. Wear suitable protective clothing. In case

of accident or if you feel unwell, seek medical advice immediately (show the label where possible). This material

and/or its container must be disposed of as hazardous waste

SECTION 3: COMPOSITION AND COMPONENT INFORMATION

 Component:
 EC No:
 CAS No:
 Hazard Class:
 Phrases:
 Concentration:

 Mercury(II) thiocyanate
 209-773-0
 592-85-8
 Acute Tox. 1
 H300, H310, H330,
 > 0.25% - < 0.50%</td>

Acute Tox. 2 H373, H400, H410 STOT RE 2 R: 26/27/28-33-50/53

Aquatic Acute 1 Aquatic Chronic 1

T+, N

Ethylene glycol 203-473-3 107-21-1 Acute Tox. 4 H302 > 95% Xn R: 22



According to Regulation (EC) No. 1907/2006 OSHA Regulation 29 CFR 1910.1200 Canadian Regulation SOR/88-66

SECTION 4: FIRST AID MEASURES

After Inhalation: Remove to fresh air. Give artificial respiration if victim is not breathing. Give oxygen if breathing is difficult.

After Skin Contact: Wash affected area with plenty of water. Immediately remove contaminated clothing.

After Eye Contact: Rinse out immediately with plenty of water for at least 15 minutes. If discomfort persists obtain medical attention.

After Swallowing: Wash out mouth thoroughly with water provided person is conscious. OBTAIN MEDICAL ATTENTION.

General Information: Remove contaminated, soaked clothing immediately and dispose of safely.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:

Appropriate Foam, Dry Chemical Powder, Carbon Dioxide

Special Risks:

Specific Hazard(s): Emits toxic fumes under fire conditions. The following may develop in event of fire: Carbon Monoxide, Carbon Dioxide, Nitrogen Oxides, Sulfur Oxides, Mercury/Mercury Oxides, Mercury Vapors

Special Protective Equipment:

Do not stay in dangerous zone without suitable chemical protection clothing and self-contained breathing apparatus.

Additional Information:

Do not direct a solid stream of water at burning material as spattering may result.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Absorb on sand or vermiculite and place in closed containers for disposal. When spilled, the floor may be slippery. Wipe up the floor completely. Clean up affected area and dispose according to local regulation. Ventilate area after material pickup is complete.

Environmental Precautions:

Do not discharge into the drains/surface waters/groundwater.

Additional Notes:

For large spillages liquids should be contained with sand or earth and both liquids and solids transferred to salvage containers. Any residues should be treated as for small spillages

SECTION 7: HANDLING AND STORAGE

Handling: Storage:

Do not breathe vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated exposure

Store at room temperature (+15 to +25°C recommended). Protect from light and moisture. Accessible only for authorized persons.



HI 93753A-0 Displacing Reagent

Safety Data Sheet
According to Regulation (EC) No. 1907/2006
OSHA Regulation 29 CF 1910.1200 Canadian Regulation SOR/88-66

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION						
Туре	Value	Source	Туре	Value	Source	
Ethylene Glyce	ol					
TWA (8hr)	52 mg/m³ (aerosol)	Belgium	Ceiling	100 mg/m ³	Canada (Ontario)	
Ceiling	127 mg/m³	Canada (Quebec)	TWA (8hr)	52 mg/m³ (vapor)	France	
TWA (8hr)	26 mg/m³	Germany	TWA (8hr)	125 mg/m³ (fume)	Greece	
TWA (8hr)	52 mg/m³	Hungary	TWA (8hr)	52 mg/m³	Italy	
TWA (8hr)	10 mg/m³ (aerosol)	Netherlands	TWA (8hr)	15 mg/m³	Poland	
Ceiling	100 mg/m ³	Portugal	TWA (8hr)	52 mg/m³	Romania	
TWA (8hr)	52 mg/m³	Spain	TWA (8hr)	52 mg/m³ (vapor)	UK	
Mercury(II) Dit	hiocyanate					
TWA (8hr)	0.025 mg (Hg)/m ³	Belgium	TWA (8hr)	0.025 mg (Hg)/m ³	Canada (Ontario)	
TWA (8hr)	0.025 mg (Hg)/m ³	Canada (Quebec)	TWA (8hr)	0.1 mg (Hg)/m ³	France	
TWA (8hr)	0.1 mg (Hg)/m ³	Germany	TWA (8hr)	0.1 mg (Hg)/m ³	Greece	
TWA (8hr)	0.08 mg (Hg)/m ³	Hungary	TWA (8hr)	0.05 mg (Hg)/m ³	Poland	
TWA (8hr)	0.025 mg (Hg)/m ³	Portugal	TWA (8hr)	0.025 mg (Hg)/m ³	Spain	
TWA (8hr)	0.01 mg (Hg)/m ³	UK	TWA (8hr)	0.025 mg (Hg)/m ³	USA (ACGIH)	
TWA (8hr)	2 mg (Hg)/m ³	USA (OSHA)				
Engineering	:					
J	neral industrial hygie otective Equipment	•				
As appropri	ate to quantity handl	ed.				
Respiratory Protection:		Prote	ective Gloves:	E	Eye Protection:	
Required when vapors/aerosols a generated. Work under hood. Industrial Hygiene:		are Rubber or plastic			Goggles or face mask	
Wash thoroughly after handling.						

0-0-1011	DID (010 11 /01/E1/04 11	
SECTION 9	PHYSICAL/CHEMICAL	PROPERTIES

Density at 20°C: 1.11 g/cm3 Appearance: Colorless liquid Odor: Almost odorless -13°C **Boiling Point:** > 190°C **Melting Point:** Solubility: Soluble pH at 20°C: NA **Explosion Limit:** Lower 3% Flash Point: ~ 115°C

Upper 15%

Thermal Decomp.: NA



Safety Data Sheet
According to Regulation (EC) No. 1907/2006
OSHA Regulation 29 CFR 1910.1200
Canadian Regulation SOR/88-66

SECTION 10: STABILITY AND REACTIVITY

Conditions to be Avoided:

Heat. Protect from moisture.

Hazardous Polymerization:

Will not occur.

Further Information:

Not available

Hazardous Decomposition Products:

In the event of fire: See section 5.

Substances to be Avoided:

Strong acids, strong oxidizing agents, strong bases, aldehydes, aluminum



According to Regulation (EC) No. 1907/2006 OSHA Regulation 29 CFR 1910.1200 Canadian Regulation SOR/88-66

SECTION 11: TOXICOLOGICAL INFORMATION

Product Toxicity

Quantitative data on the toxicity of this product is not available.

Potential Health Effects:

Inhalation: May be harmful if inhaled. Material may be irritating to mucous membranes and upper respiratory tract

Skin Contact: Irritant effects, danger of skin absorption. may be harmful if absorbed through the skin.

Eye Contact: Irritant effects.

Ingestion: Harmful if swallowed.

Further Data: The following applies to Ethylene Glycol: CHRONIC EXPOSURE: TERATOGEN Result: laboratory experiments

Not Available

have shown teratogenic effects. REPRODUCTIVE HAZARD Result: Overexposure may cause reproductive

disorder(s) based on tests with laboratory animals.

Component Toxicity

Acute Toxicity: Chronic Toxicity:

Ethylene Glycol

LD50: Oral - Rat - 4700 mg/kg

LD50: Dermal - Rabbit - 10626 mg/kg

Mercury(II) Dithiocyanate

LD50: Oral - Rat - 46 mg/kg

LD50: Dermal - Rat - 685 mg/kg

Additional Data:

APPLICABLE TO MAIN COMPONENT:

The following applies to Ethylene Glycol:

Signs and symptoms of exposure

When ingested early symptoms mimic alcohol inebriation and are followed by nausea, vomiting, abdominal pain, weakness, muscle tenderness, respiratory failure, convulsions, cardiovascular collapse, pulmonary edema, hypocalcaemic tetany, and severe metabolic acidosis. Without treatment, death may occur in 8 to 24 hours. Victims who survive the initial toxicity period usually develop renal failure along with brain and liver damage. Exposure to and/or consumption of alcohol may increase toxic effects.

Conditions aggravated by exposure

Ethylene glycol is metabolized to glycoaldehyde, glycolic acid, and glyoxal, followed by conversion to glyoxylic acid, formic acid, and oxalic acid. It has been shown that ethylene glycol is much less toxic than its metabolites. Glycolic acid is thought to be the major toxic metabolite causing acute as well as reproductive and developmental toxicity observed with ethylene glycol exposures. May cause nervous system disturbances.

APPLICABLE TO MAIN COMPONENT:

The following applies to Mercury (II) thiocyanate:

Sensitization

Sensitization: May cause allergic reaction.

Signs and symptoms of exposure

Mercury compounds have a cytotoxic and protoplasmatoxic effect. Intoxication symptoms: ACUTE: contact with eyes causes severe lesions. Swallowing and inhalation of dust damages mucous membranes of gastrointestinal and respiratory tract (metallic taste, nausea, vomiting, abdominal pain, bloody diarrhea, intestinal burns, glottal edema, aspiration pneumonia); drop in blood pressure, cardiac dysrhythmia, circulatory collapse, and renal failure; CHRONIC: inflammation of the mouth with loss of teeth and mercurial line. The principal signs manifest themselves in the CNS (impaired speech, vision, hearing and sensitivity, loss of memory, irritability, hallucinations, delirium inter alia).

Conditions aggravated by exposure

May cause nervous system disturbances.



HI 93753A-0 Displacing Reagent

Safety Data Sheet According to Regulation (EC) No. 1907/2006

OSHA Regulation 29 CFR 1910.1200 Canadian Regulation SOR/88-66

SECTION 12: ECOLOGICAL INFORMATION

Quantitative data on the ecotoxicity of this product is not available.

APPLICABLE TO MAIN COMPONENT:

The following applies to Ethylene Glycol:

Bioaccumulation potential

No indication of bioaccumulation.

Ecotoxicological effects

Fish species: Onchorhynchus mykiss (Rainbow trout): LC50 18,500 mg/L / 96 h; Leuciscus idus: LC50 > 10,000 mg/L / 48 h; Daphnia species:

Daphnia magna: EC50 74.000 mg/L / 24 h.

Additional ecological information

BOD5: 0.78 % COD: 1.29 %

APPLICABLE TO PARTIAL COMPONENT:

The following applies to inorganic Hg compounds in general:

Ecotoxicological effects

Fish species: Salmo lethal from 0.05 ppm up; P. promelas LC50: 0.19 mg/L; Hq ions toxic: fish: L. idus LC50: 0.013 mg/L; Algae: Sc.

quadricauda toxic from 0.07 mg/L up; M. aeruginosa toxic from 0.005 mg/L up.

Additional ecological information

Fish toxicity: mercury: LC50: 0.5 mg/L Hg(II) ions. Hazard for drinking water.

Luminescent bacteria toxicity:

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal: Chemical residues are generally classified as special waste and thus covered by local regulations. Contact local

authorities or disposal companies for advice. Handle contaminated packaging in the same way as the substance itself.

SECTION 14: TRANSPORTATION INFORMATION

Land: Air:

Not subject to transport regulations Not subject to transport regulations Not subject to transport regulations

SECTION 15: REGULATORY INFORMATION

Complies with European Regulations (EC) No. 1907/2006 and No. 1272/2008.

Complies with European Council Directives 67/548/EEC and 1999/45/EC.

Complies with OSHA Regulation 29 CFR 1910.1200.

Complies with Canadian Regulation SOR/88-66

SECTION 16: OTHER INFORMATION

Text of phrases under Section 3

R22: Harmful if swallowed.

R26/27/28: Very toxic by inhalation, in contact with skin and if swallowed.

R33: Danger of cumulative effects.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

H300: Fatal if swallowed.

H302: Harmful if swallowed.

H310: Fatal in contact with skin.

H314: Causes severe skin burns and eye damage.

H373: May cause damage to organs through prolonged or repeated exposure.

H330: Fatal if inhaled.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

Revision Information

Revision Date: 2013-03-13

Supersedes edition of: 2012-05-07

Reason for revision: Regulation (EC) No. 1272/2008

Compliance

Legend NA: Not Applicable

ND: Not Determined

THE INFORMATION CONTAINED HEREIN IS BASED ON THE PRESENT STATE OF OUR KNOWLEDGE. IT CHARACTERIZES THE PRODUCT WITH REGARD TO THE APPROPRIATE SAFETY PRECAUTIONS. IT DOES NOT REPRESENT A GUARANTEE OF THE PROPERTIES OF THE PRODUCT.