

# pH 5+ and 6+ Meters

These rugged, compact meters offer high accuracy at an extremely affordable price!

**Simple push-button operation** – So fast and easy, anyone can use it

**Toggle between pH and temperature in °C with a press of a button**

**Three-point pH calibration** – Choose from standard US, NIST, and pure water; gives you high ±0.01 pH accuracy

**Auto buffer recognition** – Automatically identifies the correct pH buffer for rapid calibration

**Calibration instructions are printed on back of meter** – For quick reference and added convenience

**Automatic temperature compensation (ATC)** – For the highest accuracy in changing temperature conditions

**Hold and Auto-off functions**

**Built-in stand for benchtop or long-term use**

**Protective boot** – Helps shield your meter from drops and dings

**Meter kits available** – Contain everything you need for calibration and measurement packaged in a hard carrying case—the best option.

**pH 6+ also features**

**Measurements in pH, mV, and °C** – Use for ORP (Redox) measurements

**New**



35613-52



Meters include protective rubber boot and a built-in stand.

ISO9001:2000  
CERTIFIED SUPPLIER

CE

3 year warranty  
meter only

**Specifications**

Model	pH 5+ and pH 6+ meters		pH 6+ meter only
<b>Mode</b>	pH	Temperature	mV
<b>Range</b>	0.00 to 14.00 pH	0.0 to 100.0°C	±1000 mV
<b>Resolution</b>	0.01 pH	0.1°C	1 mV
<b>Accuracy</b>	±0.01 pH	±0.5°C	±2 mV
<b>Calibration</b>	Up to 3 buffer values: choose from standard US, NIST, and pure water buffer values	Offset 0.1°C increments	±20 mV

**Temperature compensation:**  
automatic from 0.0 to 100.0°C  
**Operating temperature:** 0 to 50°C (32 to 122°F)  
**Power:** four 1.5 V AAA batteries (included), >70 hours continuous use

**Dimensions**  
**Meter:** 5½"L x 2¾"W x 1¾"H (14 x 7 x 3.5 cm)  
**Boxed:** 9¼"L x 6½"W x 3"H (23.5 x 16.5 x 7.5 cm)  
**Weight**  
**Meter:** 0.9 lb (0.4 kg); **Boxed:** 1 lb (0.5 kg)

**Ordering Information**

Catalog number	Description	Included
WD-35613-50	pH 5+ meter only	Meter, protective rubber boot, and batteries
WD-35613-20	pH 6+ meter only	
WD-35613-52	pH 5+ meter with probes	Meter; single-junction, epoxy-body pH electrode; temperature probe 35613-05; protective rubber boot; and batteries
WD-35613-22	pH 6+ meter with probes	
WD-35613-54	pH 5+ meter kit	Meter; single-junction, epoxy-body pH electrode; temperature probe 35613-05; pH buffer pouches (pH 4.01, 7.00, 10.00; and rinse water), sample bottles, protective rubber boot; batteries; and hard carrying case
WD-35613-24	pH 6+ meter kit	

**Accessories**

WD-35804-00 Replacement pH electrode  
WD-35613-05 Replacement ATC probe



Water Quality Testing



Lithographic Processes



Education