## **10DEL 7403**

## **HID Explosion Proof Rechargeable Flashlight**



November 2018

## **Optional Lens Filters:**





	Product Features
Approved for:	Class I, Division 1, Groups A, B, C, D
	Class I, Division 2, Groups A, B, C, D
	Class II, Division 1, Groups E, F, G
	Class II, Division 2, Groups E, F, G
Conforms to:	IP68 Waterproof to 3 Meters
Temperature Rating:	T-code: T4A
Lamp Type:	Xenide HID Bulb
HID Life Expectancy:	2,500 hours
Color Temperature:	6,500 K (Cool White)
Rated with Optics:	1,200 Lumens
Brightness:	5,1400 Lux @ 10 ft.
Power Consumption:	20 Watts
Ambient Temp Range:	-32° C to +45°C
Dimensions:	11.5" L
Weight:	1.9 lbs
Material/ Construction:	Aluminum Housing
Lighting Configuration:	Spot
Charging Unit:	100/240VAC 50/60Hz w/ overcharge protection, LED indicator
Battery:	2600mAh Lithium Ion Battery
Run-Time:	90 Minutes

## **Complete Kit Includes:**

- HID XP Recharge Flashlight
- AC Battery Charger (LED Indicator) Rubber Lens Cover & End Caps
- Molded Travel Case
- Straps Mounts
- Shoulder Strap
- Lens Cleaning Cloth
- User's Manual





