

# GasAlertMicro

H<sub>2</sub>S, CO, O<sub>2</sub>, SO<sub>2</sub>, Combustibles

## Multi-Gas Detector

"INNOVATORS IN GAS DETECTION"



### Protect Yourself

- ▲ Compact (2.4 x 4.0 x 1.3 in / 6 x 10 x 3.3 cm) and lightweight (7.4 oz. / 211 g)
- ▲ Integral concussion-proof boot for the most rugged environments
- ▲ Continuous LCD shows simultaneous gas concentrations for H<sub>2</sub>S, CO, O<sub>2</sub>, SO<sub>2</sub>, combustibles (0-100% LEL or 0-5.0% Methane)
- ▲ Powered by two AA alkaline or NiMH cells (run-time typically 16-18 hours)
- ▲ Provides 95 dB alarm tone and two bright wide-angled alarm bars
- ▲ Equipped with internal vibrating alarm for high noise areas
- ▲ Backlight: low light (auto); in alarm (auto); and on demand reactivation
- ▲ Four alarm levels: Instant Low and High Alarm for all gases; TWA (time weighted average) and STEL (short term exposure limit) for H<sub>2</sub>S, CO, SO<sub>2</sub>; OL (over limit alarm) for combustible gases
- ▲ Simple automatic calibration procedure; compatible with BW MicroDock II Automatic Test and Calibration System
- ▲ Records TWA, STEL and maximum exposures to gas and displays readings on command
- ▲ User selectable field options include: confidence beep, pass code protection, latching alarm, calibration due date, bump due date, "SAFE" display function, language, span concentration values, combustible sensor measurement selection (0-100%LEL or 0-5.0% v/v methane) and stealth mode
- ▲ Full function self-test of: sensor, battery and circuitry integrity; and audible/visual alarms
- ▲ Delivered ready for use with sensors, two AA alkaline cells, stainless steel alligator belt clip, calibration hose/cap and instructions



### Optional Charger Kits



**GA MicroBatt** rechargeable battery and slip-in charger cradle. The GasAlertMicro can be recharged while the battery pack is installed, or the pack can be removed for separate recharging.

### GasAlertMicro Charger II

### Ordering Information

GAMIC-4	H <sub>2</sub> S, CO, O <sub>2</sub> , LEL	GAMIC-3M	CO, O <sub>2</sub> , LEL
GAMIC-3H	H <sub>2</sub> S, O <sub>2</sub> , LEL	GAMIC-3S	SO <sub>2</sub> , O <sub>2</sub> , LEL
GAMIC-2	O <sub>2</sub> , LEL	GAMIC-2HW	H <sub>2</sub> S, LEL

#### With User-Downloadable Datalogger

Includes 32 MB Flash MultiMediaCard and software. Add suffix "-DL2-IR" for detector equipped with datalogger.

#### With Charger Kit

Includes detector, standard accessories plus charger and battery pack.  
 GAMIC-4-E3 with 4-gas detector and GA MicroBatt charger kit  
 GAMIC-4-E5 with 4-gas detector and GasAlertMicro Charger II

#### GasAlertMicro SamplerPak

Includes detector, standard accessories plus the Sampler (external motorized sampling pump), sampling hoses, sampling tubes and a carrying case.  
 GAMIC-4-SK with 4-gas detector  
 GAMIC-4-SKC with 4-gas detector and charger kit

#### Value Added Confined Space Kits

Kits include detector, standard accessories plus a hard-sided carrying case, 3 m/10 ft. sampling hose, 4-port charger, 4 NiMH batteries, 34 liter calibration gas cylinder with regulator.

#### With The Sampler motorized sampling pump

GAMIC-4-CK-IR-SP with 4-gas detector  
 GAMIC-4-CK2-IR-SP with 4-gas datalogging detector

Contact BW for available accessories

[www.gasmonitors.com](http://www.gasmonitors.com)

Email: [info@bwt.net](mailto:info@bwt.net)



# GasAlertMicro

H<sub>2</sub>S, CO, O<sub>2</sub>, SO<sub>2</sub>, Combustibles

## Multi-Gas Detector

Offering a large array of features, the ultra-compact and durable **GasAlertMicro** has set new standards in the multi-gas detection—at an economical price.

Simultaneously displaying H<sub>2</sub>S, CO, O<sub>2</sub>, SO<sub>2</sub>, or combustibles, **GasAlertMicro** is suited to a wide range of applications, including HAZMAT response, confined space entry and post-inspection fire safety.

Field-selectable user options allow **GasAlertMicro** to be customized to virtually any environment. Calibration due dates and alarm settings can be configured to meet specific industry requirements, and the pass code protect function ensures tamper-proof operation by preventing unauthorized users from accessing calibration options.

In a world of multi-gas detectors, **GasAlertMicro** truly is more for less.

"INNOVATORS IN GAS DETECTION"



**For further information:**  
**1-888-749-8878 USA**  
**1-800-663-4164 Canada**  
**+44 (0) 1869 233004 Europe**  
**+971-4-8871766 Middle East**  
**+61-438-887-232 Australia**  
**+852-2974-1783 China**  
**+65-6465-4151 South East Asia**  
**+1-403-248-9226 Other Countries**

**Corporate Headquarters**  
 2840 - 2 Avenue S.E.  
 Calgary, AB, Canada T2A 7X9  
 Phone: +1-403-248-9226  
 Fax: +1-403-273-3708

Email: info@bwt.net.com  
**www.gasmonitors.com**  
 BW1006-01-01-00-8.25x11-20050624-5359-14

## SPECIFICATIONS

Gas:	H <sub>2</sub> S	CO	O <sub>2</sub> (% by vol.)	SO <sub>2</sub>	Combustibles (Field Select)
Measuring Range:	0-100 ppm	0-500 ppm	0-25.0%	0-100 ppm	0-100 % LEL or 0-5% by vol. methane

<b>DETECTOR:</b>	1, 2, 3 or 4-gas detector
Auto zero:	Yes
Calibration:	Automatic
Backlight:	Low light (auto); alarm condition (auto); reactivation on demand
Full function self-test:	Sensor integrity, circuitry and battery; audible/visual alarms
Sensor:	Plug in, electrochemical cell (toxic and oxygen); Plug in, catalytic (LEL)
User field options:	Confidence beep, pass code protection, latching alarms, calibration due date, bump due date, "SAFE" display function, language selection, span concentration values, combustible sensor measurement selection (0-100%LEL or 0-5.0% v/v methane), enable/disable automatic O <sub>2</sub> calibration, STEL calculation period, disable backlight, battery type and stealth mode. Datalogging models only: clock, calendar and sampling rate
<b>ALARM INDICATORS:</b>	Clearly advises alarm levels both visually and audibly
Visual alarms:	Two flashing alarm bars visible from all angles LCD indicates gas present and alarm levels encountered
Audible alarm:	95 dB variable pulsed audible alarm at 1 ft. / 30 cm (typical)
Vibrator alarm:	Pulses warning in gas alarm conditions, or for any status alarms
Other:	Low battery, over range, multiple gas and missing sensor
<b>ALARM LEVELS:</b>	Instantaneous Low Alarm for all gases; instantaneous High Alarm for all gases; TWA (time weighted average) and STEL (short term exposure limit) for H <sub>2</sub> S, CO, SO <sub>2</sub> ; OL (over limit alarm) for combustible gases
<b>LCD:</b>	Continuous, alphanumeric gas readout and status display advises:
Gases monitored:	H <sub>2</sub> S, CO, O <sub>2</sub> , SO <sub>2</sub> , combustibles (0-100% LEL or 0-5.0% methane)
Gas concentration:	Simultaneous and continuously displays gas concentration(s) present (in ppm, %LEL, or % v/v) Records STEL and TWA exposures and displays on demand Records and displays peak exposure to gas and displays on demand Displayed on activation
TWA ppm or %:	
Peak ppm or %:	
Alarm setpoints:	
<b>TESTS:</b>	
Full function self-test:	Full function self-test on activation
Battery:	Continuous
<b>GENERAL SPECIFICATIONS:</b>	Rugged, composite material with integral concussion-proof boot
Operating temperature:	-4 to 122 °F / -20 to 50 °C
Temperature code:	T4 with GA MicroBatt battery pack
Humidity:	5% to 95% RH (non-condensing)
EMI/RFI:	Complies with EMC Directive 89/336/EEC
Ingress Protection:	IP65
Battery run-time:	16-18 hours on two AA alkaline cells (typical) 14-16 hours on two NiMH rechargeable cells (typical)
Size:	2.4 x 4 x 1.3 in. / 6 x 10 x 3.3 cm
Weight:	7.4 oz. / 211 g
<b>WARRANTY:</b>	Full 2 year warranty including all sensors
<b>DATALOGGER OPTIONS:</b>	User-downloadable datalogger
Data recorder:	All events and occurrences
Sampling rate:	Factory set at 5-second intervals and user-settable from 1 to 127-second intervals
Storage:	4.4 months of continuous data via 32 MB Flash MMC card (64 MB cards are also available); when full, the wraparound feature replaces oldest data with most recent data

DUE TO ONGOING RESEARCH AND PRODUCT IMPROVEMENT, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

**RATINGS AND CERTIFICATIONS:** (Intrinsic safety) Class I, Div. 1, Gr. A, B, C, D  
 American Bureau of Shipping  
**ATEX:** CE II 1 G  
 EEx ia IIC  
**IECEx:** Ex ia IIC  
**BAM:** certified for methane measuring function up to the lower explosive limit in air. BAM certified for oxygen measuring function.



- Smaller: Weighs only 7.4 oz. / 211 g
- Triple Alarm System: 95 dB audible, dual alarm bars and internal vibrator alarm
- Tougher: Equipped with integral concussion-proof boot for the most rugged environments
- Large, high-contrast LCD shows real-time gas concentrations for all four gases simultaneously and continuously
- Easy, pushbutton operation
- Flexible power operation
  - Two AA Alkaline cells (16-18 hours typical) or
  - Two NiMH cells (14-16 hours typical)
- Optional datalogger with 32 MB Flash MMC data storage



Support CD-ROM

Locally distributed by: